

DATA ACQUISITION PRODUCT-ETHERNET

2-channel Analog Output Module, with DO

Number of Output Channel: 2
Resolution: 12-bit
Input type: 0~5V/10V, 0~20mA, 4~20mA (tripartite isolation)
Digital Output:1-channel open-collector 30V(100mA maximum load)
Isolation Voltage: 3000 V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3062

1-channel Analog Output Module, with DO

Number of Output Channel: 1
Resolution: 12-bit
Input type: Output voltage and current signal at the same time
Output range: 0~5V, 0~10V, 0~20mA, 4~20mA
Digital Output:1-channel open-collector 30V(100mA maximum load)
Isolation Voltage: 3000 V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3061

2-channel Strain Gauge Input Module

Number of Input Channels: 2
Resolution: 16-bit
Input type: mV, V, mA
Sample Rate: 10 Hz
Isolation Voltage: 3000 V_{DC}
Number of Digital Input Channel: 1
Number of Digital Output Channels: 4
Support 10/100 Mbps Ethernet
Provide default or custom-built web page
Independent wire breakage detection



DAM-E3053

8-channel Thermistor Input Module

Number of Input Channels: 8DI
Resolution: 16-bit
Input type: Thermistor
Sample Rate: 10 Hz
Isolation Voltage: 3000 V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page
Independent wire breakage detection



DAM-E3048



Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıboyu Caddesi No.50 Tuzla / İstanbul

Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616

e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"

www.astraelektronik.com



DATA ACQUISITION PRODUCT-ETHERNET

6-channel Hot Resistance Input Module, with DO

Number of Input Channels: 6
Resolution: 16-bit
Sample Rate: 10 Hz
Input connect mode: 2-wire, 3-wire, 4-wire
Digital Output: 1-channel open-collector 30V(100mA maximum load)
Isolation Voltage: 3000 V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page
Independent wire breakage detection



DAM-E3046

6-channel Digital Input/6-channel AC SSR Relay Output Module

Number of Digital Input Channels: 6
Number of Relay Output Channels: 6
Digital Input: 3-channel AC SSR
Relay Output: type A
Contact Capacity: 100~250V_{AC} 1A
Isolation Voltage: 3750V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3026

6-channel Digital Input/5-channel Relay Output Module

Number of Digital Input Channels: 6
Number of Relay Output Channels: 5
Digital Input: dry/wet contact
Relay Output: type A
Contact Capacity: 250V_{AC} 1A; 30V_{DC} 2A
Isolation Voltage: 3750V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3025

6-channel Digital Input/6-channel Relay Output Module

Number of Digital Input Channels: 6
Number of Relay Output Channels: 6
Digital Input: dry/wet contact
Relay Output: type A
Contact Capacity: 250V_{AC} 1A; 30V_{DC} 2A
Isolation Voltage: 3750V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DEM-E3024



Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıbozu Caddesi No.50 Tuzla / İstanbul

Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616

e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"

www.astraelektronik.com



DATA ACQUISITION PRODUCT-ETHERNET

8-channel Digital Input/8-channel Open-collector Output Module

Number of Digital Input Channels: 8
Number of Digital Output Channels: 8
Digital Input: dry/wet contact
Digital Output: dry/wet contact
Isolation Voltage: 3750V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3021

8-channel Relay Output Module

Number of Relay Output Channels: 8
Relay Output: type A
Contact Capacity: 250V_{AC} 1A; 30V_{DC} 2A
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3018

8-channel PhotoMos Relay Output/2-channel Isolation Digital Input Module

Number of Digital Input Channels: 2
Number of Digital Input Channels: 8
Contact Capacity: 350V_{AC} 0.13A
Digital Input: wet contact
Logic level 0: +1V
Logic level 1: +4V~+30V
Isolation Voltage: 3750V
Provide default or custom-built web page



DAM-E3017

12-channel Isolation Digital Input/4-channel Open-collector Output Module

Number of Digital Input Channels: 12
Number of Digital Input Channels: 4
Digital Input: dry/wet contact
Isolation Voltage: 3750V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3016

16-channel Isolation Digital Input Module

Number of Digital Input Channels: 16
Digital Output: open-collector 30V(200mA maximum load)
Isolation Voltage: 3750V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3014



Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıboyu Caddesi No.50 Tuzla / İstanbul

Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616

e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"

www.astraelektronik.com



DATA ACQUISITION PRODUCT-ETHERNET

16-channel Isolation Digital Input Module

Number of Digital Input Channels: 16
Digital Input: dry/wet contact
Isolation Voltage: 3750V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3013

16-channel Isolation Digital Input Module

Number of Digital Input Channels: 16
Digital Input: wet contact
Logic level 0: +1V
Logic level 1: +4V~+30V
Isolation Voltage: 3750V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3012

8-channel Isolation Digital Input/1-channel Open-collector Output Module

Number of Digital Input Channels: 8
Number of Digital Output Channels: 1
Digital Output: open-collector 30V(200mA maximum load)
Isolation Voltage: 5000V
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3011

Serial Device Network-attached Servers

Network Ports: 10/100Base-T; RJ-45 Interface
Serial Ports: 1 RS-232, 1 RS-485, 1 RS-422
Transmission Speed: RS-232(300 bps ~115.2 Kbps)
RS-485/RS-422(300 bps ~230.4 Kbps)
Power Supply: +10V_{DC}~+30V_{DC} (no conditioning)



DAM-E3220

8-channel high-speed Analog Input Module

Input Range: -10~10V, -5~5V, 0~10V, 0~5V
Number of Input Channels: 8SE/4DI
Resolution: 12-bit
Sample Rate: 500 Hz
Isolation Voltage: 3000 V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3056BH



Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıboyu Caddesi No.50 Tuzla / İstanbul

Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616
e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"
www.astraelektronik.com



DATA ACQUISITION PRODUCT-ETHERNET

8-channel Analog Input Module, with DO

Number of Input Channels: 8SE/8DI
Resolution: 16-bit
Input type: mV, V, mA
Sample Rate: 10 Hz
Digital Output: 1-channel open-collector 30V(100mA maximum load)
Isolation Voltage: 3000 V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3058F

8-channel high-speed Analog Input Module

Input Range: -10~10V, -5~5V, 0~10V, 0~5V
Number of Input Channels: 8SE/4DI
Resolution: 16-bit
Sample Rate: 500 Hz
Isolation Voltage: 3000 V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page



DAM-E3056AH

1-channel Hot Resistance Input Module, with DO

Number of Input Channels: 1
Resolution: 16-bit
Sample Rate: 10 Hz
Input connect mode: 2-wire, 3-wire, 4-wire
Digital Output: 1-channel open-collector 30V(100mA maximum load)
Isolation Voltage: 3000V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page
Independent wire breakage detection



DAM-E3041B

8-channel Thermocouple Input Module, with DO

Number of Input Channels: 8DI
Resolution: 16-bit
Sample Rate: 10 Hz
Digital Output: 1-channel open-collector 30V (100mA maximum load)
Isolation Voltage: 3000V_{DC}
Support 10/100 Mbps Ethernet
Provide default or custom-built web page
Independent wire breakage detection



DAM-E3039F



Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıboyu Caddesi No.50 Tuzla / İstanbul

Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616

e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"

www.astraelektronik.com



DATA ACQUISITION PRODUCT-ETHERNET

2-channel Frequency/Counter Input Module

Counter Input

Number of Channels: independent 2-channel

Resolution: 32-bit

Maximum Frequency Input: 100 KHz

Input: 3750V Isolation or Non-isolation

Programmable digital filter: Yes

LED Display: 5-bit

Provide 10/100 Mbps Ethernet



DAM-E3070D

3-channel Hot Resistance Input Module, with DO

Number of Input Channels: 3

Resolution: 16-bit

Sample Rate: 10 Hz

Input connect mode: 2-wire, 3-wire, 4-wire

Digital Output:1-channel open-collector 30V(100mA maximum load)

Isolation Voltage: 3000 V_{bb}

Support 10/100 Mbps Ethernet

Provide default or custom-built web page

Independent wire breakage detection



DAM-E3043



Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıboyu Caddesi No.50 Tuzla / İstanbul

Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616

e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"

www.astraelektronik.com

