## **PXI CHASSIS**

Number of Slots: 14 Number of System Slots: 1

Number of PXI Peripheral Slots: 13

Power Supply: AC

Total Available Power: 500W

Accepts both 3U and Compact PCI Modules: Yes

Operating Temperature: 0'C~50'C Relative Humidity: 10% ~ 90%

Size: 258mm\*448mm\*177mm (L\*W\*H)
4U height rack mount or desktop installation
Compatible with PXI, Rev2.2 specifications
Compatible with IEEE 1101.10 formal standard

Meet the PICMG2.0 specification Cooling fan with a strainer

Temperature, voltage and fan monitoring LED

Number of Slots: 10 Number of System Slots: 1 Number of PXI Peripheral Slots: 9

Power Supply: AC

Total Available Power: 400W

Accepts both 3U and Compact PCI Modules: Yes

Operating Temperature: 0~50'C Relative Humidity: 10%~90%

4U height rack mount or desktop installation Compatible with PXI, Rev2.2 specifications Compatible with IEEE 1101.10 formal standard

Meet the PICMG2.0 specification Cooling fan with a strainer

Temperature, voltage and fan monitoring LED

Number of Slots: 6

Number of System Slots: 1 Number of PXI Peripheral Slots: 5

Power Supply: AC

Total Available Power: 400W

Accepts both 3U and Compact PCI Modules: Yes

Operating Temperature: 0~50'C Relative Humidity: 10%~90%

4U height rack mount or desktop installation Compatible with PXI, Rev2.2 specifications Compatible with IEEE 1101.10 formal standard

Meet the PICMG2.0 specification Cooling fan with a strainer

Temperature, voltage and fan monitoring LED



PXIC-7314



**PXIC-7310** 



PXIC-7306



## Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıboyu Caddesi No.50 Tuzla / İstanbul
Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616
e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"
www.astraelektronik.com

