

TABLET PC

Low-power, low radiation touch tablet PC, 10.4" screen

32-bit RISC processor, working frequency 200MHz
Memory: 64MByte
SDRAM Nor Flash: 64MByte
RS-232: 2, one of them with hardware handshake signals
RS-485: 1
USB: one host and one client
Ethernet: 100M Industrial Ethernet interface
Display: 10.4 "TFT LCD
Resolution: 640 * 480/800 * 600
4-wire resistive touch screen
Resolution: continuous
Transmission rate: 85%
Service life: 100 million times
Power Supply: DC 24V/1.5A
Operating Temperature: 0'C~ +50'C
Storage Temperature: -10'C~ +60'C



HMI9910

Low-power, low radiation touch tablet PC, 10.4" screen

- ☐ 32-bit RISC processor, working frequency 520MHz
- ☐ Memory: 64MByte
- ☐ SDRAM Nor Flash: 32MByte
- ☐ RS-232: 2, one of them with hardware handshake signals
- ☐ RS-485: 1
- ☐ USB: one host and one client
- ☐ Ethernet: 100M Industrial Ethernet interface
- ☐ Display: 10.4 "TFT LCD
- ☐ Resolution: 640 * 480/800*600
- ☐ Maximum number of colors: 65536 colors
- ☐ 4-wire resistive touch screen
- ☐ Resolution: continuous
- ☐ Transmission rate: 85%
- ☐ Service life: 100 million times
- ☐ Power Supply: DC 24V/1.5A
- ☐ Operating Temperature: 0'C ~ +50'C
- ☐ Storage Temperature: -10'C ~ +60'C



HMI9110



Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıboyu Caddesi No.50 Tuzla / İstanbul

Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616

e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"

www.astraelektronik.com



TABLET PC

Low-power, low radiation touch tablet PC, 6.4" screen

- ☐ 32-bit RISC processor, working frequency 200MHz
- ☐ Memory: 64MByte
- ☐ SDRAM Nor Flash: 64MByte
- ☐ RS-232: 2, one of them with hardware handshake signals
- ☐ RS-485: 1
- ☐ USB: one host and one client
- ☐ Ethernet: 100M Industrial Ethernet interface
- ☐ Display: 6.4" TFT LCD
- ☐ Resolution: 640 * 480
- ☐ Maximum number of colors: 65536 colors
- ☐ 4-wire resistive touch screen
- ☐ Resolution: continuous
- ☐ Transmission rate: 85%
- ☐ Service life: 100 million times
- ☐ Power Supply: DC 24V/1.5A
- ☐ Operating Temperature: 0°C ~ +50°C
- ☐ Storage Temperature: -10°C ~ +60°C



HMI9906

Low-power, low radiation touch tablet PC, 8.4" screen

- ☐ 32-bit RISC processor, working frequency 200MHz
- ☐ Memory: 64MByte
- ☐ SDRAM Nor Flash: 64MByte
- ☐ RS-232: 2, one of them with hardware handshake signals
- ☐ RS-485: 1
- ☐ USB: one host and one client
- ☐ Ethernet: 100M Industrial Ethernet interface
- ☐ Display: 8.4" TFT LCD
- ☐ Resolution: 640 * 480/800*600
- ☐ Maximum number of colors: 65536 colors
- ☐ 4-wire resistive touch screen
- ☐ Resolution: continuous
- ☐ Transmission rate: 85%
- ☐ Service life: 100 million times
- ☐ Power Supply: DC 24V/1.5A
- ☐ Operating Temperature: 0°C ~ +50°C
- ☐ Storage Temperature: -10°C ~ +60°C



HMI9908



Astra Elektronik Sanayi İthalat ve Ticaret Limited Şirketi

Postane Mahallesi Yalıboyu Caddesi No.50 Tuzla / İstanbul

Tel: +90 216 5740612/13/14/15 Faks: +90 216 5740616

e-mail: astra@astraelektronik.com GPS: N 40°49'10.7" E 29°17'29.2"

www.astraelektronik.com

